


15KV INTERFACE



1. Load break probes are shipped assembled.
2. Ground cable included; #5 stranded Cu, 37" long.
3. Each arrester is shipped with a packet of silicone grease, wiping cloth and instruction sheet.

PHYSICAL CHARACTERISTICS

WEIGHT LBS./ (kg)	Fault Withstand
3.0/ (1.4)	20 kA

ELECTRICAL CHARACTERISTICS

CATALOG NO.	RATING kV-RMS	MCOV kV-RMS	F.O.W. kV-CREST	MAX SWITCH. kV-CREST	MAX DISCHARGE VOLTAGE (kV-CREST)				
					1.5 kA	3 kA	5 kA	10 kA	20 kA
8132B0003J001	3	2.55	10.0	7.9	8.5	8.8	9.3	10.2	12.9



MACLEAN POWER SYSTEMS

www.maclepower.com

GAPLESS METAL OXIDE
ZE ELBOW DISTRIBUTION ARRESTER
8132B0003J001
3 KV RATED, 2.55 KV MCOV

THIS DRAWING IS THE PROPERTY OF MACLEAN POWER SYSTEMS AND EMBODIES A CONFIDENTIAL PROPRIETARY DESIGN IN WHICH MACLEAN POWER SYSTEMS RETAINS ALL PATENTS AND PROPRIETARY RIGHTS, INCLUDING EXCLUSIVE RIGHT OF USE, MANUFACTURE AND SALE. BY ACCEPTING THIS DRAWING, THE RECIPIENT AGREES NOT TO DISCLOSE, REPRODUCE OR USE ANY INFORMATION CONTAINED HEREIN WITHOUT THE PRIOR WRITTEN CONSENT OF MACLEAN POWER SYSTEMS.

DATE 09/29/11

DRAWN EJM

CHECKED

8132B0003J001

DO NOT SCALE DRAWING

SHEET 1 OF 1