



NOTES

1. MATERIAL -
 CLAMP BODY & KEEPERS - ALUMINUM ALLOY A356-T6.
 HARDWARE - STEEL, HOT DIP GALVANIZED.
 COTTER PINS - 302 STAINLESS STEEL.
2. FITTINGS (ADD SUFFIX TO CATALOG NO.)
 "-S" FOR SOCKET EYE FITTING
 "-C" FOR CLEVIS FITTING
 "-N" FOR NO FITTING
 "-NLP" FOR NO FITTING LESS CLEVIS PIN
 "-BC" FOR BOLT, NUT & COTTER
 "-RYCI" FOR 90 DEG. Y-CLEVIS EYE
 "-S8" FOR 52-8 SOCKET EYE FITTING

CATALOG NO.	LENGTH A	HEIGHT B	EAR WIDTH C	GROOVE DIA. D	PIN DIA. E	LIP ANGLE α	ULT. STR.
ACFS-244-20-20	20	3 1/4	2 1/2	2.37 2.44	5/8	17°	20,000 LBS.
ACFS-244-33-36	33	4 1/2	3 1/2	2.37 2.44	3/4	28°	36,000 LBS.
ACFS-244-21-40	21	3 3/4	3 1/2	2.37 2.44	3/4	16.2°	40,000 LBS.
ACFS-230-21-50	21	3 5/8	3 3/8	2.16 2.30	7/8	18°	50,000 LBS.

NO.	DATE	DESCRIPTION	BY	CKD
3	5/22/08	ADDED ACFS-230-21-50	BS	
2	7/28/06	ADDED ACFS-244-21-40	BS	
1	6/12/01	ACFS2443336 ULT. STR. WAS 46K	BC	

BETHEA POWER PRODUCTS
 PELHAM, ALABAMA

A MacLean Power Systems Co.

ALUMINUM CORONA FREE
 SUSPENSION CLAMP

DATE: 6/12/01	SCALE: NONE	NO. AC-0135-58	R/3	SH 1
BY: BC	BY: []	BY: []		OF 1

REVISIONS