



NOTES

1. MATERIAL -  
 CLAMP BODY & KEEPERS - ALUMINUM ALLOY A356-T6.  
 HARDWARE - STEEL, HOT DIP GALVANIZED.  
 COTTER PINS - 302 STAINLESS STEEL.
2. FITTINGS (ADD SUFFIX TO CATALOG NO.)  
 "-S8" FOR 52-8 SOCKET EYE FITTING  
 "-N" FOR NO FITTING  
 "-BC" FOR BOLT, NUT, AND COTTER KEY

CATALOG NO.	LENGTH A	HEIGHT B	EAR WIDTH C	GROOVE DIA. D	PIN DIA. E	LIP ANGLE $\alpha$	ULT. STR.
ACFS-241-15-50	15	3 5/8	3 1/2	2.41	7/8	15°/35°	50,000
ACFS-248-15-50	15	3 5/8	3 1/2	2.48	7/8	15°/35°	50,000
ACFS-254-15-50	15	3 3/4	3 1/2	2.54	7/8	15°/35°	50,000
ACFS-280-15-50	15	3 3/4	3 1/2	2.80	7/8	15°/35°	50,000

NO.	DATE	DESCRIPTION	BY	CKD
2	7/9/11	ADDED ACFS-254-15-50	BS	
1	12/16/08	ADDED ACFS-280-15-50	BS	

**BETHEA POWER PRODUCTS**  
 PELHAM, ALABAMA A MacLean Power Systems Co.

ALUMINUM CORONA FREE  
 SUSPENSION CLAMP

REVISIONS

DATE: 11/14/06	SCALE: NONE	NO. AC-0135-68	R/2	SH.1 OF 1
BY: BS	BY: BS			