



CATALOG NUMBER	ULTIMATE STRENGTH POUNDS	FOR INSULATOR CLASS	DIMENSIONS-INCHES				WGT. LBS. PER C.
			A	B	C	D	
SYC-56	30,000	ASA 52-3&5	1 5/8	2 3/4	2 1/8	3/4	321
SYC-56F	30,000	ASA 52-3&5 Fog Type	1 3/4	4	2 1/8	3/4	340
SYC-86	40,000	ASA 52-8	1 11/16	3	2 1/4	3/4	360
SYC-87	50,000	ASA 52-8 & 11	1 7/8	3	2 1/2	7/8	385
SYC-207	45,000	IEC 20mm	2	4 3/8	2 1/2	7/8	410
SYC-249	66,000	IEC 24mm	3	4 5/8	3 1/16	1 1/8	

AVAILABLE WITH SPHERICAL SHIELD NUT. TO SPECIFY, ADD SUFFIX "-S" TO CATALOG NUMBER. EXAMPLE: SYC-56-S.

MATERIAL - NODULAR IRON

BENT BOLT - STEEL - AISI 4140

NUT - STEEL ASTM A563 OR EQUAL

COTTER PIN - AISI 302 STAINLESS STEEL

ALL FERROUS PARTS - HOT DIP GALVANIZED PER ASTM-A153

4	8-1-84	SYC-86 "A" DIM. WAS 1 5/8"	BI	BC	RELIABLE/BETHEA POWER PRODUCTS INC. PELHAM, ALABAMA
3	5-16-84	ADDED 52-11 TO SYC-87	BI	BC	
2	8-9-79	REDRAWN	VLP	JM	TYPE SYC SOCKET Y-Clevis
		NEW CAT. NO.	RC	BI	
1	5-31-78	CHANGED FROM OLD CAT. NO. TO			
NO.	DATE	DESCRIPTION	BY	CKD	
REVISIONS					DATE: 11-16-76
					SCALE: NONE
					NO. AC-6249
					R/4 SH. 1 OF 1