



NOTES

1. MATERIAL -
 CLAMP BODY & KEEPERS - ALUMINUM ALLOY A356-T6.
 HARDWARE - STEEL, HOT DIP GALVANIZED.
 COTTER PINS - 302 STAINLESS STEEL.
2. FITTINGS (ADD SUFFIX TO CATALOG NO.)
 "-S" FOR SOCKET EYE FITTING
 "-C" FOR CLEVIS FITTING
 "-N" FOR NO FITTING
 "-NLP" FOR NO FITTING LESS CLEVIS PIN
 "-BC" FOR BOLT, NUT & COTTER
 "-RYCI" FOR 90° Y-CLEVIS EYE
 "-6" FOR 3/4" DIA. PIN (EX. CF-184-N-6)
 "L" FOR NON-ROTATING PIN (EX. CF-184L-N)

CATALOG NO.	LENGTH A	HEIGHT B	EAR WIDTH C	CLAMPING RANGE		PIN DIA. D	LIP ANGLE α	ULT. STR.
				MIN.	MAX.			
CF-111	10 1/2	2 1/4	1 7/8	1.000	1.110	5/8	15°	25,000
CF-120	10 1/2	2 1/4	1 7/8	1.110	1.200	5/8	15°	25,000
CF-143	10 1/2	2 7/16	1 7/8	1.200	1.430	5/8	15°	25,000
CF-163	11 1/2	2 5/8	2 3/8	1.430	1.630	5/8	15°	25,000
CF-184	11 1/2	2 7/8	2 3/8	1.630	1.840	5/8	15°	25,000

NO.	DATE	DESCRIPTION	BY	CKD
7	1/28/02	ADDED "6" AND "L" SUFFIX	BS	
6	4/28/99	CF-184 "C" DIM WAS 2-1/2"	DC	
5	7/14/93	ADDED "RYCI" SUFFIX NOTE	BS	
4	11/2/92	REDRAWN	BS	BC



MACLEAN POWER SYSTEMS
A Maclean-fogg Company

CORONA FREE SUSP. CLAMP
 CF-SERIES

REVISIONS

DATE: 2/7/78	SCALE: NONE	NO. AC-6362-1	R/	SH.1
BY: BI	BY: BC	BY: KS		OF 1