



NOTES

1. MATERIAL -
 CLAMP BODY & KEEPERS - ALUMINUM ALLOY A356-T6.
 HARDWARE - STEEL, HOT DIP GALVANIZED.
 COTTER PINS - 302 STAINLESS STEEL.
2. FITTINGS (ADD SUFFIX TO CATALOG NO.)
 "-S" FOR SOCKET EYE FITTING
 "-C" FOR CLEVIS FITTING
 "-N" FOR NO FITTING
 "-NLP" FOR NO FITTING LESS CLEVIS PIN
 "-BC" FOR BOLT, NUT & COTTER
 "-RYCI" FOR 90° Y-CLEVIS EYE

CATALOG NO.	LENGTH A	HEIGHT B	EAR WIDTH C	CLAMPING RANGE		PIN DIA. D	LIP ANGLE α	ULT. STR.
				MIN.	MAX.			
CFA-088	13	2 7/16	1 7/8	0.80	0.88	5/8	30°	25,000
CFA-095	13	2 7/16	1 7/8	0.880	0.950	5/8	30°	25,000
CFA-111	13	2 3/8	1 7/8	1.000	1.110	5/8	30°	25,000
CFA-120	13	2 1/4	1 7/8	1.110	1.200	5/8	30°	25,000
CFA-143	13	2 7/16	1 7/8	1.200	1.430	5/8	30°	25,000
CFA-184	13 3/4	2 7/8	2 3/8	1.630	1.840	5/8	30°	25,000
CFA-204	13 3/4	3 1/8	2 1/2	1.820	2.075	5/8	30°	25,000

9	11/13/13	ADDED CFA-184	BS
8	10/14/03	ADDED TORQUE & U-BOLT ϕ	BS
7	7/18/03	ADDED CFA-088	BS
6	4/28/99	CFA-204 "C" WAS 2-3/4"	BS
5	11/2/92	REDRAWN	BS BC
NO.	DATE	DESCRIPTION	BY CKD

MACLEAN POWER SYSTEMS
A Maclean-fogg Company

CORONA FREE SUSP. CLAMP
CFA-SERIES

DATE: 12/20/78	SCALE: NONE	NO. AC-6362-2	R/9	SH.1 OF 1
BY: BI	BY:	BY:		

REVISIONS