



Pat. No. 3,915,056

**HIGH STRENGTH AND CORROSION
RESISTANT, A356-T6 ALUMINUM ALLOY.**

WASHERS ARE AVAILABLE IN SQUARE OR RECTANGULAR SHAPES TO MAXIMIZE BEARING SURFACE. THE ALUMINUM ALLOY WASHERS HAVE A PATENTED TAPER WHICH PREVENTS DAMAGE TO THE WOOD FIBERS AT THE WASHERS EDGE. THIS MEANS MORE CONTACT AT POLE.

CATALOG NUMBER	MAXIMUM BOLT SIZE INCHES MM	DIMENSIONS				WGT/C LBS KG	MATERIAL
		INCHES					
		A	B	C	D		
WC-22-6	3/4	2-1/4	2-1/4	5/16	13/16	11	ALUMINUM ALLOY
	19	57.2	57.2	7.9	20.6	5.0	
WC-23-6	3/4	2-1/4	3-1/2	9/16	13/16	25	ALUMINUM ALLOY
	19	57.2	88.9	14.3	20.6	11.3	
WC-33-5 +	5/8	3	3	7/16	11/16	25	ALUMINUM ALLOY
	16	76.2	76.2	11	17.5	11.3	
WC-33-6	3/4	3	3	9/16	13/16	24	ALUMINUM ALLOY
	19	76.2	76.2	14.3	20.6	10.9	
WC-34-7 +	7/8	3	4	9/16	15/16	39	ALUMINUM ALLOY
	22	76.2	101.6	14.3	23.8	17.7	
WC-35-7	7/8	3	5	9/16	15/16	47	ALUMINUM ALLOY
	22	76.2	127.0	14.3	23.8	21.3	
WC-44-6 +	3/4	4	4	9/16	13/16	44	ALUMINUM ALLOY
	19	101.6	101.6	14.3	20.6	20.00	
WC-44-7	7/8	4	4	9/16	15/16	56	ALUMINUM ALLOY
	22	101.6	101.6	14.3	23.8	25.4	
WC-44-8	1	4	4	11/16	1-1/16	72	ALUMINUM ALLOY
	25	101.6	101.6	17.5	27	32.7	

+ REA APPROVED

RELIABLE/BETHEA POWER PRODUCTS INC.
PELHAM, ALABAMA

Washers

NO.	DATE	DESCRIPTION	BY	CKD
REVISIONS				

DATE: 8-4-81	SCALE: NONE	NO.	R/O	SH. 1
DWN. BY: BT	CKD. BY: JJM	APR. BY:	AC-6695	OF 2