



ASSEMBLY NUMBER	RATED STRENGTH	CHARPY LEVEL	STANDARD PACK	WEIGHT
SYCR-87F	50,000 LBS	-	10	4.80
SYCR-87F-CH1	50,000 LBS	1	10	4.80
SYCR-87F-CH2	50,000 LBS	2	10	4.80

NOTES:

- MATERIAL - BODY: FORGED STEEL
HARDWARE: HOT DIP GALVANIZED PER ASTM A-153
COTTER PIN: AISI 302 STAINLESS STEEL
- MARKING: MPS SYCR87F
- SPHERE NUT: TO INCLUDE SPHERE NUT ADD SUFFIX "S" (SYCR-87F-S)

CH1: CHARPY LEVEL 1 MEETS MIN ENERGY ABSORPTION OF 20J AT -20°C
(15 FT-LBS AT -4°F)

CH2: CHARPY LEVEL 2 MEETS MIN ENERGY ABSORPTION OF 30J AT -30°C
(22 FT-LBS AT -22°F)

NO.	DATE	DESCRIPTION	BY	CKD

REVISIONS



MACLEAN POWER SYSTEMS
A Maclean-fogg Company

90° SOCKET Y-CLEVIS
CAT. NO. SYCR-87F

DATE: 11/13/18	SCALE: NONE	NO. AC-7162-5	R/0	SH.1 OF 1
BY: WCL	BY: []	BY: []		