



- NOTES:
1. MATERIAL - DUCTILE IRON, HOT DIP GALVANIZED.
OPTIONAL HARDWARE: STEEL, HOT DIPPED GALVANIZED.
 2. FOR TAPPED 3/8"-16 THD. HOLE FOR EXTERNAL GROUNDING DEVICE ADD SUFFIX "-3-16" TO CAT. NO. (EX. IACB-12-5-3-16).
FOR GROUNDING DEVICE (1) 3/8" CARRIAGE BOLT, (2) FLATWASHERS, (1) LOCKWASHER, & (1) NUT, ADD SUFFIX "-GB" TO CAT. NO. (EXAMPLE IACB-12-5-GB).
 3. FOR HARDWARE (1/2" HEX BOLT, WASHER, LOCK WASHER & NUT) ON OUTSIDE EARS (2 SETS) ADD SUFFIX "-B" (EXAMPLE IACB-12-5-B).
 4. FOR 13/16" DIAMETER HOLES ON OUTSIDE EARS (3), ADD SUFFIX "-6" (EXAMPLE IACB-12-5-6).

NO.	DATE	DESCRIPTION	BY	CKD
1	9/17/23	ADDED OPTIONS 3 & 4	KMK	

REVISIONS

RELIABLE/BETHEA POWER PRODUCTS INC.
PELHAM, ALABAMA

CUT-OUT & ARRESTOR BRACKET
CAT. NO. IACB-12-5

DATE: 5/6/03	SCALE: NONE	NO. AC-7963	R/1	SH.1 OF 1
BY: DM	BY: []	BY: []		