



ASSEMBLY NUMBER	RATED STRENGTH	CHARPY LEVEL	STANDARD PACK	WEIGHT
ASH-66A-BC	60,000 LBS	-	20	2.32
ASH-66A-BC-CH1	60,000 LBS	1	20	2.32
ASH-66A-BC-CH2	60,000 LBS	2	20	2.32

**NOTES:**

- MATERIAL - BODY: FORGED STEEL  
HARDWARE: HOT DIP GALVANIZED PER ASTM A-153  
COTTER PIN: AISI 302 STAINLESS STEEL
- MARKING: MPS M-335-82, ASH-66A
- SPHERE NUT: TO INCLUDE SPHERE NUT ADD SUFFIX "S" (ASH-66A-BC-S)

CH1: CHARPY LEVEL 1 MEETS MIN ENERGY ABSORPTION OF 20J AT -20°C  
(15 FT-LBS AT -4°F)

CH2: CHARPY LEVEL 2 MEETS MIN ENERGY ABSORPTION OF 30J AT -30°C  
(22 FT-LBS AT -22°F)

NO.	DATE	DESCRIPTION	BY	CKD
1	3/16/18	CHANGED TO NEW FORMAT	BKS	

**REVISIONS**



**MACLEAN POWER SYSTEMS**  
A Maclean-fogg Company

ANCHOR SHACKLE  
CATALOG NO. ASH-66A-BC SERIES

DATE: 1/31/18	SCALE: NONE	NO. AC-8548-1	R/1	SH.1 OF 1
BY: KMK	BY:	BY:		