



ASSEMBLY NUMBER	RATED STRENGTH	CHARPY LEVEL	STANDARD PACK	WEIGHT
ASH-67-BC	60,000 LBS	-	15	2.88
ASH-67-BC-CH1	60,000 LBS	1	15	2.88
ASH-67-BC-CH2	60,000 LBS	2	15	2.88

NOTES:

- MATERIAL - BODY: FORGED STEEL
HARDWARE: HOT DIP GALVANIZED PER ASTM A-153
COTTER PIN: AISI 302 STAINLESS STEEL
- MARKING: MPS M-335-29, ASH-67
- SPHERE NUT: TO INCLUDE SPHERE NUT ADD SUFFIX "S" (ASH-67-BC-S)

CH1: CHARPY LEVEL 1 MEETS MIN ENERGY ABSORPTION OF 20J AT -20°C
(15 FT-LBS AT -4°F)

CH2: CHARPY LEVEL 2 MEETS MIN ENERGY ABSORPTION OF 30J AT -30°C
(22 FT-LBS AT -22°F)

NO.	DATE	DESCRIPTION	BY	CKD
1	3/21/18	CHANGED TO NEW FORMAT, WAS BC8549-1	BKS	

REVISIONS



MACLEAN POWER SYSTEMS
A Maclean-fogg Company

ANCHOR SHACKLE
CATALOG NO. ASH-67-BC SERIES

DATE: 3/21/18	SCALE: NONE	NO. AC-8549-1	R/1	SH.1 OF 1
BY: BKS	BY:	BY:		