



NOTES:

1. MATERIAL - STEEL, ASTM A572 GR. 50 HOT DIP GALVANIZED PER ASTM A153
2. ULTIMATE STRENGTH - 50,000 LBS.
3. MARKING - Y1VS050S, 50K (3/8" LETTERS)
4. REMOVE ALL BURRS AND RAGGED EDGES
5. ALL HOLES TO BE DRILLED
6. CIRCLED DIMENSIONS ARE FOR REFERENCE ONLY AND ARE NOT TO BE USED IN FABRICATION
7. TOLERANCES - $\pm 1/16$ " UNLESS NOTED.
8. EST. WT. 9.6 LBS.
9. PLATE THICKNESS - 3/4".

STANDARD TOLERANCES (UNLESS OTHERWISE NOTED)			
	DECIMAL (IN)	FRACTIONS (IN)	ANGLES (DEG)
MACHINE	.XX $\pm .01$	$\pm 1/64$	$\pm 1/2$
FABRICATION		$\pm 1/16$	± 1
CASTING/FORGING	± 0.031	$\pm 1/32$	$\pm 1/2$

NO.	DATE	DESCRIPTION	BY	CKD
3	8/12/13	ADDED NOTE 9 PLATE THICKNESS	LMV	WCL
2	8/8/13	CORRECTED PART # & STAMP INSTR.	LMV	WCL
1	8/11/10	Was AM8070-2, stamped 50K rating	WCL	WCL

REVISIONS

RELIABLE/BETHEA POWER PRODUCTS INC.
PELHAM, ALABAMA

YOKE PLATE
CAT. NO. Y1VS050S

DATE: 4/30/10	SCALE: NONE	NO. AM-6645-46	R/3	SH1 OF 1
BY: WCL	BY: WCL	BY: WCL		