



≡ NOTES ≡

1. MATERIAL - STEEL, ASTM A572 GR. 50.
2. TOLERANCES - 1/16" UNLESS NOTED
3. REMOVE ALL BURRS AND RAGGED EDGES FROM YOKE AND ALL HOLES, BOTH SIDES.
4. FINISH - HOT DIP GALVANIZE PER ASTM A153.
5. ULTIMATE STRENGTH - 40,000 LBS.
6. MARKING - Y2TT040S1800, 40K(3/8" LETTERS)
7. EST. WT. 14.5 LBS.
8. ALL HOLES TO BE DRILLED, NO PUNCHING  
PLATE TO BE FLAME CUT, NO SHEARING

STANDARD TOLERANCES			
(UNLESS OTHERWISE NOTED)			
	DECIMAL (IN)	FRACTIONS (IN)	ANGLES (DEG)
MACHINE	.XX ±.01    .XXX ±.005	+ -    1/64	+ -    1/2
FABRICATION		+ -    1/16	+ -    1
CASTING/FORGING	+ -    0.031	+ -    1/32	+ -    1/2

NO.	DATE	DESCRIPTION	BY	CHKD
1	11/15/12	CATALOG NO. WAS Y1TT040S1800	BS	WCL
REVISIONS				

**MACLEAN POWER SYSTEMS**  
*A Maclean-Jogg Company*

TRIANGULAR TANGENT STEEL  
YOKE; CAT. NO. Y2TT040S1800

DATE: 11/22/11	SCALE: NONE	NO. AM-6725-60	R/1	SH.1
DWN. BY: BS	APP. BY: WCL	APR. BY:		OF 1