



### NOTES

1. MATERIAL - NODULAR IRON ASTM A536 - 67T GRADE 604018 AS EXTENDED AND MODIFIED BY BETHEA SPECIFICATION 55-11-6.
2. FINISH - HOT DIP GALVANIZED PER ASTM - A153.
3. FOR ANSI 52-3 & 52-5 INSULATORS.

CATALOG NUMBER	ULTIMATE STRENGTH (POUNDS)	DIMENSIONS IN INCHES				WGT. LBS. PER C.
		A	B	C	D	
SI-500	18,000	1/2	2 3/16	1 5/8	11/16	108
SI-625	20,000	5/8	2 3/16	1 5/8	11/16	111
SI-750	25,000	3/4	2 3/16	1 5/8	11/16	113
SI-875	30,000	7/8	2 3/16	1 5/8	11/16	115
SI-1125	30,000	1 1/8	2 3/16	1 5/8	11/16	118
SI-1375	30,000	1 3/8	2 3/16	1 1/2	11/16	122
SI-1375-G				1 5/8	13/16	128
SI-1750	30,000	1 3/4	2 3/16	1 1/2	11/16	130
SI-2000	30,000	2	2 3/16	1 1/2	11/16	138
SI-2187	30,000	2 3/16	2 3/16	1 1/2	11/16	146
SI-2500	30,000	2 1/2	2 3/16	1 1/2	11/16	168
SI-1062	30,000	1 1/16	2 5/16	1 5/8	11/16	117

4	3-25-83	ADDED SH 3, SI-2000	BI	BC
3	6-1-80	ADDED SI-1375-G	BI	BC
2	2-15-80	SI-1062 WAS SI-1000	BI	UM
1	1-14-80	ADDED SI-1000	VLP	BI

**RELIABLE/BETHEA POWER PRODUCTS INC.**  
PELHAM, ALABAMA

## SOCKET EYE

NO.	DATE	DESCRIPTION	BY	CKD	DATE: 12-1-77	SCALE: NONE	NO.
		REVISIONS					
					DWN. BY: J.T.S.	CKD. BY: B.I.	APR. BY:

ASM-260

R/4 SH1 OF 4