



CATALOG NUMBER	ULTIMATE STRENGTH POUNDS	DIMENSIONS-INCHES								WGT. LBS. PER C.
		A	B	C	D	E	F	G	H	
RCE-55-750A	18,000	3/4	2 7/8	1 1/2	5/8	11/16	1 1/2	11/16	1 1/4	140
RCE-55-625	18,000	5/8	2 7/8	1 1/2	5/8	11/16	1 1/2	11/16	1 1/4	135
RCE-55-750	30,000	3/4	2 3/8	2 1/2	5/8	1	2	11/16	1 3/8	145
RCE-55-1125	25,000	1 1/8	2 7/8	1 5/8	5/8	13/16	1 7/8	11/16	1 5/16	148
RCE-55-1375	25,000	1 3/8	2 7/8	1 1/2	5/8	13/16	1 7/8	11/16	1 7/8	171
RCE-55-1750	30,000	1 3/4	2 7/8	1 3/8	5/8	13/16	1 7/8	11/16	1 7/8	190
RCE-56-1375	25,000	1 3/8	2 7/8	1 1/2	5/8	13/16	1 7/8	13/16	1 7/8	165
RCE-55-2000	30,000	2	2 7/8	1 5/8	5/8	13/16	1 7/8	11/16	1 7/8	205
RCE-55-2187	30,000	2 3/16	2 7/8	1 5/8	5/8	13/16	1 7/8	11/16	1 7/8	210
RCE-55-2500	30,000	2 1/2	2 7/8	1 5/8	5/8	11/16	1 7/8	11/16	1 5/16	215
RCE-65-687	30,000	11/16	3	2 3/8	3/4	7/8	1 3/4	11/16	1 3/4	145
RCE-55-1000	30,000	1	2 9/16	1 3/4	5/8	13/16	2	11/16	1 11/16	200
RCE-66-812	40,000	13/16	3 1/2	2 1/4	3/4	1	2 5/16	13/16	1 5/8	190
RCE-66-1000	30,000	1	2 9/16	1 3/4	3/4	13/16	2	13/16	1 11/16	198
RCE-66-1125	30,000	1 1/8	3	1 3/4	3/4	15/16	1 7/8	13/16	2 1/8	200
RCE-78-1125	75,000	1 1/8	5 1/2	4	7/8	1 1/8	3	1 1/16	3	550
RCE-99-1250	80,000	1 1/4	4	4	1 1/8	1 1/2	3 1/4	1 1/4	2 3/8	580

FOR BOLT, NUT AND COTTER INSTEAD OF CLEVIS PIN AND COTTER, SPECIFY BY ADDING SUFFIX "-BC" TO CATALOG NUMBER.

Ductile Iron - Hot Dip Galvanized

				RELIABLE/BETHEA POWER PRODUCTS INC. <small>PELHAM, ALABAMA</small>	
3	5-18-83	ADDED RCE-55-750A	BI	BC	TYPE RCE Clevis Eye 90°
2	7-7-81	ADDED RCE-55-1000	BI	BC	
1	7-17-80	ADDED RCE-56-1375	RI	JM	
NO.	DATE	DESCRIPTION	BY	CKD	
REVISIONS					DATE: 9-4-79 SCALE: N.T.S. NO. ASM-315 YLP BI R/3 SH. 3 OF 4