



CATALOG NUMBER	RATED STRENGTH	CHARPY LEVEL	A	B	C	SERIES STAMP	STANDARD PACK	WEIGHT
CL-4	30,000 LBS	N.A.	1"	2 1/4"	1/2"	M-6224-1	100	.440
CL-4-CH1	30,000 LBS	1	1"	2 1/4"	1/2"	M-6224-1	100	.440
CL-5	40,000 LBS	N.A.	1"	3 1/4"	5/8"	M-6224-2	50	.920
CL-5-CH1	40,000 LBS	1	1"	3 1/4"	5/8"	M-6224-2	50	.920
CL-6	60,000 LBS	N.A.	1"	3 1/2"	3/4"	M-6224-3	25	1.330
CL-6-CH1	60,000 LBS	1	1"	3 1/2"	3/4"	M-6224-3	25	1.330
CL-6-CH2	60,000 LBS	2	1"	3 1/2"	3/4"	M-6224-3	25	1.330
CL-8	110,000 LBS	N.A.	1 1/4"	4"	1"	M-6224-4	20	2.775
CL-8-CH1	110,000 LBS	1	1 1/4"	4"	1"	M-6224-4	20	2.775
CL-8-CH2	110,000 LBS	2	1 1/4"	4"	1"	M-6224-4	20	2.775
CL-10	150,000 LBS	N.A.	2 1/2"	7"	1 1/4"	M-6224-5	5	7.301
CL-10-CH1	150,000 LBS	1	2 1/2"	7"	1 1/4"	M-6224-5	5	7.301
CL-10-CH2	150,000 LBS	2	2 1/2"	7"	1 1/4"	M-6224-5	5	7.301

NOTES:

- MATERIAL — BODY: FORGED STEEL  
FINISH: HOT DIP GALVANIZED PER ASTM A-153
  - MARKING: MPS, CATALOG NUMBER, RATED STRENGTH, SERIES STAMP
- CH1: CHARPY LEVEL 1 MEETS MIN ENERGY ABSORPTION OF 20J AT -20°C  
(15 FT-LBS AT -4°F)
- CH2: CHARPY LEVEL 2 MEETS MIN ENERGY ABSORPTION OF 30J AT -30°C  
(22 FT-LBS AT -22°F)

NO.	DATE	DESCRIPTION	BY	CKD
1	01/16/19	Consolidated 5 different drawings to 1.	EM	
REVISIONS				



**MACLEAN POWER SYSTEMS**  
A Maclean-fogg Company

CHAIN LINK  
CL SERIES

DATE: 1/16/19	SCALE: NONE	NO. ASM-6224	R/1 SH.1 OF 1
BY: EM	BY:	BY:	