



NOTES

1. MATERIAL : BODY AND KEEPER ; ALUMINUM ALLOY A356-T6
HARDWARE : STEEL, HOT DIP GALVANIZED
COTTER PIN ; STAINLESS STEEL
2. CONDUCTOR RANGE
MIN.— T/2 SPARROW (#2 - 6/1 ACSR) .316" DIA. MIN.
MAX.— T/2 IBIS (397.5 - 26/7 ACSR) .783" DIA
3. ULTIMATE STRENGTH : 25,000 LBS. MINIMUM ULTIMATE
4. FOR BOLT, NUT, AND COTTER PIN ADD SUFFIX "BNK"
5. FOR ANSI 52-5 SOCKET EYE FITTING USE SI-1750



MacLean Power Systems
BIRMINGHAM , ALABAMA

DRAWN BY:
EHJ

APPROVED BY: VEP
CHECKED BY: VEP

SCALE:
N.T.S.

SC-T2-397.5
SUSPENSION CLAMP FOR T/2 CONDUCTOR

NO.	DATE	DESCRIPTION	BY
2	05-06-22	MIN WAS .398"	BKS
1	01-09-90	REVISED PER FINAL DESIGN	EJ

DATE:
11-2-88

DRAWING NO:
CEA-2502

SH: 1
OF: 1 R / 2