



NOTES

1. MATERIAL : BODY & KEEPER ; ALUMINUM ALLOY A356-T6  
HARDWARE ; STEEL, HOT DIP GALVANIZED  
COTTER PIN ; STAINLESS STEEL  
GROMMETS ; NEOPRENE
2. CONDUCTOR RANGE  
MAX.— T/2 ROOK (636 - 24/7 ACSR) .977 DIA.  
MIN.— T/2 IBIS (397.5 - 26/7 ACSR) .783 DIA.
3. THIS SUSPENSION CLAMP IS CORONA FREE WHEN USED WITH CORRECTLY  
DESIGNED CONNECTING HARDWARE
4. ULTIMATE STRENGTH : 25,000 LBS. MINIMUM
5. FOR BOLT, NUT, AND COTTER ADD SUFFIX "BC" (CSC-T2-636-BC)



MacLean Power Systems  
BIRMINGHAM , ALABAMA

DRAWN BY: E H J

APPROVED BY:  
CHECKED BY:

SCALE: N.T.S.

CSC-T2-636  
CORONA FREE SUSPENSION CLAMP  
FOR T/2 CONDUCTOR

NO.	DATE	DESCRIPTION	BY
1	10-29-90	2 15/32 WAS 3 1/8, 2 3/16 WAS 2 1/4	EJ
REVISIONS			

DATE: 06-01-90

DRAWING NO: CEA-2710

R/1