



CATALOG NO.	DIM. "A"	CARRIAGE BOLT
SF-BC-6	13/16"	1/2 X 1 1/2"
SF-BC-7	15/16"	1/2 X 1 1/2"
SF-BC-1	1-1/16"	1/2 X 1 1/2"
SF-BC-4	1-1/16"	1/2 X 2"
SF-BC-1.312	1-5/16"	1/2 X 1 1/2"

UNLESS SPECIFIED
 DIM. TOL. - $\pm 1/16"$
 HOLE TOL. - $\pm 1/32"$
 ANGLES - $\pm 1^\circ$

NOTES:

- 1.0 - MATERIALS:
 - 1.1 - A-36 STEEL.
- 2.0 - HARDWARE:
 - 2.1 - (1) 1/2" x 1-1/2" OR 1/2" X 2" CARRIAGE BOLT.
 - 2.2 - (1) 1/2" SPLIT LOCK WASHER; STEEL.
 - 2.3 - (1) 1/2" HEX NUT; STEEL.
 - 2.4 - (1) BC-4 BONDING CLAMP; DUCTILE IRON.
- 3.0 - FINISH:
 - 3.1 - HOT DIP GALVANIZED PER ASTM A-153 SPECS.
- 4.0 - CONDUCTOR RANGE = .16" - .44"

PROPRIETARY

This information is confidential and is the property of Maclean Power Systems. It may not be made public or reproduced except that the customer may make copies for use solely in the installation, maintenance, and operation of products supplied by Maclean Power Systems.



MacLean Power Systems

DRAWN BY: AH	APPROVED BY: WCL CHECKED BY: WCL	SCALE: NONE
--------------	-------------------------------------	-------------

"SF-BC" SERIES
 BONDING CLIP

NO.	DATE	DESCRIPTION	BY
04	8-09-12	ADDED SF-BC-4 & REVISED TABLE.	KK
03	8-10-99	BDR TO MPS, ADDED CAPTIVE TO NOTE	MH
02	4-22-92	REVISED & REDRAWN.	JW
01	8-15-86	REVISED & REDRAWN.	AH
NO. REVISIONS			

DATE: 8-15-86	DRAWING NO: CFA-567	SH: 1 OF: 1	R/4
---------------	---------------------	----------------	-----