


Size	Drawing Number		
A	GD-DE-S110x		
Rev	Revised By	Revision Date	ECO #
C	SG	8/1/2019	D9542



Wire Material:
Galvanized Steel Wire per ASTM A475
See Chart for Galv Class

For use on: Galvanized Steel Strand, Utility Grade, High Strength, and Extra High Strength cable

MPS Catalog #	Size	Mean-Diameter (in)	Applied Length (in)	Cross Over Mark Color		Items per Carton	Est Wt Carton (lbs.)	Rod Count	Galv Coat
				A	B				
DE-S1104	1/4" EHS	0.248 - 0.256	25	YELLOW	YELLOW	100	38	5	B
DE-S1106	5/16" EHS	0.307 - 0.315	31	BLACK	BLACK	60	40	5	B
DE-S1107	3/8" EHS	0.37 - 0.378	35	ORANGE	ORANGE	40	38	6	B
DE-S1108	7/16" EHS	0.433 - 0.441	38	GREEN	-	25	34	6	B
DE-S1104LA	1/4" EHS	0.24 - 0.259	23	YELLOW	-	100	31	4	A
DE-S1104L	1/4" EHS	0.248 - 0.256	24	YELLOW	-	100	34	4	B
DE-S1106L	5/16" EHS	0.307 - 0.315	27	BLACK	-	60	39	4	B
DE-S1107L	3/8" EHS	0.37 - 0.378	29	ORANGE	-	40	38	5	B

Note:
Left Hand Lay Standard.
All dimensions are reference and in inches.

This drawing contains confidential information that is the property of MacLean Power, L.L.C. ("MacLean"). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability.

		Drawing Description: Galvanized Steel Strand Deadends	
		Drawing Number: GD-DE-S110x	Drawn by: SG Dsgn Date: 12/31/18