MacLean TM POWER SYSTEMS			MacLean Power Systems upplier Requirements Manual		
Document #:	COR-PLCY-00002	Revision:	H		
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023		

# **Supplier Requirements Manual**

This manual describes MacLean Power Systems expectations for its suppliers to ensure that purchased material and/or service meet MacLean Power Systems requirements.





















#### **TABLE OF CONTENTS**

Letter from CEO	3
Section 1: Introduction to Manual	4
Section 2: Supplier Qualification and Evaluation Process	4
Section 3.0: Business Management System Requirements	7
Section 4.0: Product Qualification (APQP)	10
Section 5.0 Manufacturing/Process Control	15
Section 6.0: Change Control	17
Section 7.0: Rejected Product and Corrective Action	19
Section 8.0: Packaging, Labeling & Delivery	20
Section 9.0 Cost of Poor-Quality Recovery Policy	25
Appendix A: MPS Supplier Requirement Manual Sign Off Form	26



Letter from CEO Return to Top





July 2023

Subject: Supplier Requirements Manual

This Supplier Requirements Manual contains expectations for suppliers who provide products and services to the locations of MacLean Power Systems. It serves to ensure that purchased material and service meet MacLean Power Systems requirements. It has been endorsed by the leadership of MacLean Power Systems locations.

In today's manufacturing environment, product that is identified to be non-conforming at receiving or during production causes serious disruptions of the production and shipping schedules resulting in high production costs. MacLean Power Systems requires suppliers to control the quality of material provided.

This manual applies to all suppliers providing any Maclean Power Systems location with materials (raw, finished, WIP), products, processing and services including intra-company suppliers. The general requirements outline herein do not supersede any conflicting requirements that may be stated in the MacLean Power Systems Terms and Conditions, contracts, long term agreements, drawings, applicable engineering specifications and/or process specifications.

This manual has been designed to work in conjunction with Maclean Power Systems Terms and Conditions and Purchas Orders. Conducting business with MacLean Power Systems requires adherence to this manual.

If there are any questions regarding this manual and/or other requirement, please do not hesitate to reach out to the appropriate location Purchasing and/or Quality Department Contact.

Thank you for your continued support.

Steve Scharnhors

President & CEO

MacLean Power Systems

P: 855.MPS.SHIP

macleanpower.com

481 MUNN RD SUITE 300 FORT MILL, SC 29715

MacLean MacLea		MacLe Supplier I	MacLean Power Systems Supplier Requirements Manual		
Document #:	COR-PLCY-00002	Revision:	Н		
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023		

### **Section 1: Introduction to Manual**

Return to Top

In today's manufacturing environment, product that is found to be non-conforming at receiving or during production, causes serious disruptions of the production and shipping schedules, resulting in high production costs. MacLean Power Systems requires suppliers to control the quality of material provided.

This manual applies to all suppliers providing any MacLean Power Systems location with materials (raw, finished, WIP), products, processing, and services, including intra-company Suppliers, and when applicable, to Supplier sub-tier sources. The general requirements outlined herein do not supersede conflicting requirements in the MacLean Power Systems Terms and Conditions, contract, or drawing, including applicable engineering specifications and process specifications, or applicable long-term agreement(s). In conducting business with MacLean Power Systems, you are acknowledging adherence to this manual. If you have any questions regarding any of these standard procedures, you should discuss them with your supplier quality contact at MacLean Power Systems.

This manual is designed to work in conjunction with the Terms and Conditions document. Please refer to that document for any further details or requirements.

## Section 2: Supplier Qualification and Evaluation Process

Return to Top

All suppliers to MacLean Power Systems shall be qualified suppliers. The extent of the qualification process is dependent upon the criticality of product purchased and other factors determined by MacLean Power Systems. Suppliers are provided a reasonable period to comply with the requirements of this manual.

The qualification process in its most complete form consists of the following:

- 1. Request to Add a New Vendor Set Up.
- Suppliers may be asked to complete a Supplier Self-Assessment Form.
- 3. Suppliers shall agree to the terms of the Supplier Requirements Manual (SRM) by completing the SRM Sign-off Form.
- 4. An on-site audit may be conducted by MacLean Power Systems personnel or their authorized agents, if required. Approved suppliers are added to the Approved Supplier List.
- 5. Suppliers should supply a copy of relevant certifications.

MacLean Power Systems periodically reevaluates suppliers using the Scorecard Procedure.

MacLean TM POWER SYSTEMS			MacLean Power Systems upplier Requirements Manual		
Document #:	COR-PLCY-00002	Revision:	Н		
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023		

Section	2.2: Request to Add New Vendor Set Up	Return to
		lop

In the early stages of supplier selection process, potential suppliers may be sent the Request to Add New Vendor Set Up. This request solicits general information about the company such as location(s), size, capabilities, and financial stability as well as detailed questions regarding the Company's quality management system and quality history.

Section 2.2: Supp	olier Self Audit Form	Return to
		<u>Top</u>

When a new supplier is being considered, they may be sent a Supplier Self-Assessment Form. Suppliers complete the Self-Assessment Form and return it along with a copy of their valid QMS and other certifications as applicable. MacLean Power Systems will review

MacLean MacLea			MacLean Power Systems oplier Requirements Manual		
Document #:	COR-PLCY-00002	Revision:	Н		
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023		

the assessment to determine if the documented quality system meets MacLean Power System's requirements and if any further steps are required.

Section 2.3: SRM Sign-Off Form	Return to
	<u>Top</u>

Suppliers are to read this manual and return the SRM Sign-off Form (Last page of this document) acknowledging they have read, understand, and will comply with these requirements.

S	Section 2.4: On-Site Audit	Return to
		Top

Some suppliers of products or services, where it is determined that the self-assessment is not adequate to qualify a supplier, an on-site audit of the supplier's facility may be performed.

If the audit team determines that the supplier meets MacLean Power Systems' requirements, MacLean Power Systems qualifies the supplier who is then added to the Approved Supplier List and able to bid on new business and supply production materials.

If the assessment finds areas of concern Suppliers will be required to address the concerns to the satisfaction of MacLean Power Systems within an agreed upon time frame.

Section 2.5: Periodic Re-Evaluation	Return to
	<u>Top</u>

MacLean Power Systems periodically reviews current suppliers using the Scorecard Procedure. If requested, suppliers shall make their facility available for on-site process verification by MacLean Power Systems personnel, with reasonable notice.

Scorecards will be issued a minimum of annually and at a greater frequency as determined by MPS location. Suppliers are to respond and address any areas of concern.

MacLean Power Systems evaluates current production suppliers based on the following criteria (Scorecard Procedure):

- Supplier Quality Concerns Rejected Parts (SCARs or NMRs)
- Delivery and Shipping Discrepancies
- Productivity

These metrics may be modified by the local site to meet the requirements of the site or the work being performed \*\*



MacLean™ Trenton P						y Sup <sub>l</sub> ce Sui	plier mmary	,
Supplier #:	122080				02.5	Score:	100	Α
Supplier Name:	Alabast	er Branc	h Plant		Q,Z		100	^
	Q1	Q2	Q3	Q4	YTD	1	Rub	oric
QUALITY	<b>Q1</b> 65	<b>Q2</b> 65	Q3 -	Q4 -	YTD 65		Rub 101 - 120	oric A+
QUALITY DELIVERY		-	Q3 - -	Q4 - -				
	65	65	Q3 - -	- - -	65		101 - 1 <b>2</b> 0	A+
DELIVERY	65 32 -	65 35 -	Q3 - - -	- - -	65 33 -		101 - 120 97 - 100	A+ A
DELIVERY PRODUCTIVITY	65	65	Q3 - - -		65		101 - 120 97 - 100 90 - 96	A+ A B

#### **Quarter Details**

	CATEGORY	MAX	APR.	MAY	JUN.
<b>×</b>	Rejected Parts	25	25	0	0
QUALITY	Complaints	30	30	0	0
ΝŊ	Responsiveness	10	10	0	0
0	Quality Score	65	65	0	0
	On-Time Delivery	29	29	0	0
<b>≻</b>	Premium Freight Out	2	2	0	0
DELIVERY	Paperwork	2	2	0	0
ä	DMN Generated	1	1	0	0
	On-Time Response	1	1	0	0
	Delivery Score	35	35	0	0
Ł	Cost Reduction	5	0	0	0
Ē	Improved Lead Time	5	0	0	0
5	Local Safety Stock	5	0	0	0
PRODUCTIVITY	Value Added Engineering	5	0	0	0
R	Productivity Score (Bonus)	20	0	0	0
TOTAL	Monthly Score	120	100	-	-

**Supplier Rating Detailed Calculations** 

Scorecard final scores are the total score for Quality, Delivery, and Productivity.

Maclean Power Systems may conduct Supplier Improvement Meetings for underperforming suppliers who are required to attend and present containment/corrective actions. Underperforming suppliers are identified on the Supplier Scorecard.

<b>*</b>	MacLean TM POWER SYSTEMS		an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

# **Section 3.0: Business Management System Requirements**

Return to Top

MacLean Power Systems recognizes the latest version of internationally recognized Management Systems: ISO 9001; IATF 16949; and ISO 14001 and other Interested Party requirements as they apply to our businesses. Accordingly, all MacLean Power Systems suppliers are required to establish documents and implement effective production, quality, and management systems compliant with these requirements, including those specified by the customer.

This manual reinforces the MacLean Power Systems Purchase Order Terms and Conditions.

Section 3.1 Quality Manual / Certification	Return to
	<u>Top</u>

Suppliers are required to maintain an effective quality management system.

Registration to the latest version of ISO 9001 Quality Management System is a minimum requirement. In addition, suppliers shall meet all other requirements of this manual (a grace period may be provided to newly acquired MPS locations and their suppliers to comply with the requirements of this manual).

Specially designated small suppliers lacking resources to implement ISO 9001 may have certain elements waived by MacLean Power Systems or may be chosen for a supplier development program supported by MacLean Power Systems. Local Sites may be contacted to obtain the written criteria for granting a waiver.

Whenever a supplier receives a quality standard certification for the first time or for renewal, a copy of the certification must be sent to the MacLean Power Systems site Quality Department. Follow the instructions as provided to you by your site contact. If the supplier provides products or services to more than one MacLean Power Systems site, each site must be provided a copy of this document.

If certification is rescinded, suppliers must notify the MacLean Power Systems site Quality Department in writing within five business days.

MacLean Power Systems reserves the right to verify supplier compliance to ISO 9001, IATF 16949, or ISO 14001 on-site for those suppliers identified as having a high impact to safety, fit, form, function, quality and or customer down-time. Any MacLean Power Systems Customer reserves the right to visit supplier's manufacturing site to verify quality of purchased products and review supporting documentation.

Suppliers shall strive to continually improve its products, processes, and systems. Suppliers shall conduct regular reviews of:

<b>**</b>	MacLean TM POWER SYSTEMS	MacLe Supplier I	an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

- Environmental, Health, and Safety (EHS) systems and objectives
- Quality policy and objectives
- Audit results
- Data analysis
- Corrective and Preventive actions
- Risk Assessments (includes supply chain processes)
- The Global Materials Management Operations Guidelines/Logistics Evaluation (Global MMOG/LE), or an equivalent
- Contingency plans (EDI, Transportation, Packaging, Equipment, etc.)

The process of continuous improvement must be included in the goals and objectives of the entire supplier organization. Continuous improvement can reduce potential CAPAS and prevent possible non-conformances.

NOTE: Additional MacLean Power Systems site(s) or Business Units(s) may mandate additional requirements on their Purchase Order or other written supply agreements (e.g., Terms and Conditions).

Section 3.2: Control of Sub-Tier Suppliers	Return to
	<u>Top</u>

Suppliers are responsible for the quality of materials and components provided by their subtier suppliers and sub-contractors. MacLean Power Systems suppliers shall impose controls on their sub-tier suppliers that provide quality results and documentation comparable to the controls applied to suppliers by MacLean Power Systems. The extent of the controls may vary, depending on the nature and complexity of the product and processes, but should normally include:

- Compliance to certifications as applicable
- Evaluation and qualification of sub-tier supplier facilities
- Controls to ensure that raw materials used meet MacLean Power System's requirements
- Controls to ensure that the sub-tier suppliers of components used are those approved by MacLean Power Systems, where applicable
- Ensure that sub-tier suppliers have an Electronic Static Discharge (ESD) control program that meets or exceeds the needs of MacLean Power Systems if the parts or materials are ESD sensitive
- Part qualification, including first article inspection and process capability studies as applicable
- Ensure that sub-suppliers can meet capacity requirements through capacity verification calculations and associated documentation
- Control of drawings/revisions

<b>*</b>	MacLean TM	MacLe Supplier F	an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	H
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

- Control of nonconforming material
- Corrective action and preventive action programs
- A continuous quality improvement program

Where appropriate, MacLean Power Systems may specify the sub-tier suppliers that may be used, evaluated, and qualified the sub-tier supplier's facilities, and assist suppliers in controlling the sub-tier supplier. Typically, this occurs when the sub-tier supplier is an essential component of the supply-chain process. MacLean Power Systems reserves the right/judgement to evaluate the quality system and records of such sub-tier suppliers as necessary. In the event of MacLean Power Systems involvement, it does not absolve suppliers of the ultimate responsibility for the quality performance of their sub-tier suppliers.

Section 3.3: Social Responsibility	Return to
	<u>Top</u>

Suppliers shall maintain policies for themselves as well as their suppliers to meet the following social requirements:

#### 1. Ethics

- a. Do not partake in offering, providing, or receiving bribes, gifts, or other benefits with the intent or effect of influencing business or governmental decision-making
- b. Report any illegal activities and encourage employees to do so
- c. Practice fairness in all aspects of the business
- d. Promote good citizenship activities

#### 2. Diversity

- a. Encourage woman or minority owned suppliers
- b. Non-discrimination policy based on race, nationality, ethnicity, religion, disability, sex, sexual orientation, or age

#### 3. Human Rights

- a. Comply with the United Nations Universal Declaration of Human Rights
- b. Comply with the Conventions of the International Labor Organization
- c. Competitive pay rates for the area
- d. Follow local labor laws
- e. Allow workers to freely assemble and associate
- f. The use of child, convict, slave, or other forced labor is strictly prohibited.
- g. Compliance with the Conflict Minerals rules is required, and accurate and thorough completion of all questionnaires is required of the vendor and its upstream suppliers.

#### 4. Safety

a. Require Personal Protective Equipment such as ear plugs, safety

MacLean MacLean S POWER SYSTEMS		MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

glasses, protective clothing, safety shoes, etc.

- b. Monitor safety occurrences
- c. Proactively find and eliminate potential hazards
- 5. Philanthropy
  - a. Donate gifts from suppliers to local charities
  - b. Community involvement
- 6. Confidentiality
  - a. Information related to MacLean Power Systems shall be maintained confidentially.

Section 3.4: Environmental, Health, and Safety Responsibili	Return to
	<u>Top</u>

All MacLean Power Systems suppliers shall have an effective Environmental Health and Safety (EHS) management program in place. A robust EHS program reduces operational impact on human health and the environment in a sustainable manner

Suppliers are required to maintain policies for themselves as well as their suppliers to meet the following environmental requirements:

- 1. ISO 14001 and ISO 45001. Third party Registration to ISO 14001 and ISO 45001 is strongly recommended.
- 2. All MacLean Power Systems suppliers shall work proactively to reduce the environmental footprint of MacLean Power Systems products by complying with the environmental requirements of our customers.
- 3 Suppliers shall work to reduce the impact of packaging waste materials, substances, recyclability, life cycle assessment (LCA) data, etc., are to be reported according to legal requirements and/or those of MacLean Power Systems customers. Suppliers shall comply with all applicable EHS regulations.
- 4. Maximize use of renewable resources
- 5. Integrate environmental management tools into business plans, including life-cycle assessment and costing, environmental management standards, and eco-labelling.

MacLean MacLean S POWER SYSTEMS		MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

## **Section 4.0: Product Qualification (APQP)**

Return to Top

All suppliers shall produce advanced quality plans to support the development of new products and/or services, in accordance with the guidelines in the AIAG Advanced Product Quality Planning and Control Plan (APQP) Manual.

All suppliers are required to report the status of their APQP activities on a defined agreed upon basis.

All suppliers are required to utilize the MacLean Power Systems prescribed APQP format, when indicated.

All suppliers are required to participate in the MacLean Power Systems APQP process, when asked.

Where required, suppliers are to provide updated Team Feasibility Commitment Form (as per AIAG APQP Manual Appendix D) within seven days of request. Include capacity verification calculations / sheets to confirm adequate capacity to produce product.

The feasibility process for the supplier is critical to ensure the successful launch of a product or service.

Failure to provide Suppliers Team Feasibility Form on a timely basis ma/y result in a Supplier Corrective Action Report (S-CAR).

S	Section 4.1: New Product/Process Launch Readiness	Return to
		<u>Top</u>

MacLean Power Systems site Purchasing and Quality both monitor and manage selected suppliers from new product/process release through the start of production. New product/process launch readiness measures are implemented to ensure that suppliers can produce in accordance with the requirements of the Purchase Order. Suppliers are required to stay on launch containment for as long as Maclean Power Systems is on launch containment, or for the prescribed interval set forth between MacLean Power Systems and the supplier. Suppliers must have written approval to exit launch containment. Data showing compliance to requirements may be required before exit is approved.

Section 4.2: Supplier Risk Assessment	Return to
	Top

MacLean Power Systems site Purchasing, Quality and Program Management may conduct internal Supplier Risk Assessments to determine which supplier's products are to be identified as "selected or critical suppliers" and will be tracked by site Quality. Input from

MacLean TM POWER SYSTEMS		MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

Corporate Quality and Purchasing as well from other sites may be reviewed as needed. Criteria includes, but is not limited to:

- Product / process complexity
- New product / complexity for Maclean Power Systems
- Past product / process concerns
- Suppliers launch history
- Impact on final product
- New supplier production location

- Past warranty concerns
- New supplier
- New product / process for supplier
- Product environmental impact
- Mergers, acquisitions, or affiliations associated with a supplier

Section 4.3: Component Review Meeting	Return to
	<u>Top</u>

Component review meetings may be held with selected suppliers to identify key product/process characteristics that must be statistically monitored to ensure stability.

Component review meetings will determine packaging and labeling requirements. Shipping trials must be conducted to evaluate the ability of the packaging to preserve product quality.

Section 4.4: Supplier Document / Process Review	Return to
	<u>Top</u>

Supplier Document/Process review documents will be used to gage the progress of the suppliers' product quality plan.

Section 4.5: Production Trial Run	Return to
	<u>Top</u>

All suppliers are required to perform a Production Trial Run (Run at Rate) prior to launch. A Production Trial Run is performed to verify that a supplier's actual production process can meet program volumes at an acceptable quality level. This Production Trial Run shall be performed by suppliers and included with the PPAP and/or APQP documentation, if requested by the MacLean Power Systems site.

Suppliers should manage tooling, equipment and facilities such that during a 7-calendar day week:

- Average Production Weekly (APW) capacity requirements are to be met by operating the tooling, equipment and facilities based on a 5-day work week.
- Maximum Production Weekly (MPW) capacity requirements are to be met by operating the tooling, equipment and facilities based on a 6-day work week.

<b>*</b>	MacLean TM	MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

The MacLean Power Systems site using the ordered materials/services may perform on site Production Trial Runs when indicated. Circumstances that may lead to Production Trial Runs include new supplier to MacLean Power Systems, new process to a current supplier, location shift from one site to another, upgraded tooling, increased production requirements and/or previous history with suppliers or the component. When necessary, site Supplier Quality Assurance will schedule the on-site Production Trial Run with the supplier's senior manager. Site Purchasing may be contacted in case they wish to send a representative as well.

A completed Supplier Process Sign-Off (PSO) may be performed in conjunction with the Production Trial Run. A PSO may be performed when required by an end customer, when the program is high risk to MacLean Power Systems, or if the supplier has been deemed high risk on the program or when initial sample parts indicate potential manufacturing concerns. In addition, a PSO may be performed when the supplier is new to MacLean Power Systems, when the process is new to suppliers, if a process change is made in the production facility or if previous history with the supplier and/or component warrants it.

Section 4.6: Launch Support	Return to
	<u>Top</u>

During any program launch at MacLean Power Systems or MacLean Power Systems customer's production facility, selected suppliers may be required to provide on-site representation.

Suppliers' launch support representative(s) must be knowledgeable, capable, and empowered to make decisions. When launch support is requested, the supplier representative shall stay on location until concerns have been resolved.

Section 4.7: Supplier Document / Process Review	Return to
	<u>Top</u>

Where required, suppliers must submit request for and obtain full approval from MacLean Power Systems per the latest requirements of the AIAG Production Part Approval Process (PPAP) Manual.

Sample submissions are to be Level 3 unless otherwise specified.

PPAP documents are to be submitted to site Quality in compliance to the Supplier PPAP Checklist for approval. PPAP documentation must be provided in the latest revision of the AIAG PPAP forms.

Electronic prints utilized for PPAP submission must be sent in PDF format.

Five (5) certified samples (one per tool/cavity) with the dimensional report are to be submitted to each using or manufacturing facility for fit and function approval (unless

<b>1</b>	MacLean TM POWER SYSTEMS	MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

otherwise specified).

Suppliers must provide evidence of materials, substances, and recyclability data submission International Material Data System (IMDS) with every PPAP submission. PPAP approvals will not be granted for packages that do not contain this information.

Suppliers are responsible for cascading this requirement and collecting data from their respective sub-suppliers.

Suppliers of an incorrect IMDS shall be responsible for all costs related to the inaccurate submission, including any warranty from the end use customer due to the use of prohibited and restricted materials, the cost of any testing or re-validation that may be required.

If requested by MacLean Power Systems, or MacLean Power Systems customer, suppliers shall furnish a complete submission, on a yearly basis. At minimum, each supplier shall provide a new warrant, new dimensional and new material certifications as an annual validation, upon request from MacLean Power Systems or the receiving plant. This shall be provided within seven days of the request.

All PPAP documentation, including material certifications and pertinent test data, must be submitted in English, unless otherwise agreed upon. Any translation costs required will be billed back to suppliers, and a S-CAR issued to cover the translation costs and any pertinent administration fees.

Upon expiration of the second interim approval, MacLean Power Systems may issue a S-CAR to suppliers.

Where applicable Maclean Power Systems owned tooling must have an asset tag attached, showing "Property of MacLean Power Systems". Verification of this tag should be provided with the PPAP package.

Section 4.8: Raw Material / Chemical Suppliers	Return to
	<u>Top</u>

Suppliers are to submit technical information and samples to the using MacLean Power Systems location via the site Quality contact per agreement with the site.

Suppliers are required to supply Certificates of Authenticity (COA) for each shipment of product. The COA must be emailed to the receiving location to be reviewed prior to off-loading of material.

Upon request, copies of this documentation must be made available for MacLean Power Systems personnel review.

<b>*</b>	MacLean TM	MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

Lot tracking information must be submitted for all materials.

All Suppliers shall retain samples of both incoming raw materials as well as finished product for a minimum time equal to the shelf life of the lot, or six months after the production of the lot. Where actual samples are not possible, e.g., unstable, /or volatile chemicals, suppliers must maintain records of analysis.

All Suppliers must conform to the labeling requirements as described in the Terms and Conditions.

SDS (safety data sheet) must be made accessible or provided for each material provided.

Section 4.9: CQI-9 Heat-Treat System Assessment	Return to
	Top

For all applicable components, it is a requirement that suppliers use heat-treat sub-suppliers who comply with the CQI-9 Heat-Treat System Assessment or comply themselves. Suppliers must ensure that they or their sub-supplier complete the survey, meet the minimum requirements of the standard, and maintain their compliance. A copy of the finished survey shall be included in the PPAP package. An updated copy must be submitted each year or as agreed upon at the site level. The assessment can be found at <a href="https://www.aiag.org">www.aiag.org</a>.

Section 4.10: CQI-11 Plating System Assessment	Return to
	<u>Top</u>

For all applicable components, it is a requirement that suppliers use plating sub-suppliers who comply with the CQI-11 Plating System Assessment or are complying themselves. Suppliers must ensure that they or their sub-supplier(s) complete the survey, meet the minimum requirements of the standard, and maintain their compliance. Plating processes affected by this requirement include, but are not limited to:

- Zinc
- Zinc Alloy Plating
- Surface conditioning of metals for decorative plating
- Surface conditioning of ABS and PCABS plastics for decorative plating
- Decorative plating
- Mechanical plating (all copper silver, gold, passivation, and any and all metal plating addition processes)

A copy of the finished survey shall be included in the PPAP package. An updated copy must be submitted each year or as agreed upon at the site level.

<b>**</b>	MacLean TM POWER SYSTEMS	MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

Section 4.12: CQI-12 Coating System Assessment	Return to
	<u>Top</u>

For all applicable components, it is a requirement that suppliers use coating sub-suppliers who comply with the CQI-12 Coating System Assessment or comply themselves. Suppliers must ensure that they, or their sub-supplier, complete the survey, meet the minimum requirements of the standard, and maintain their compliance. Coating processes affected by this requirement include, but are not limited to:

- Aqueous cleaning
- Mechanical cleaning
- Phosphating
- Powder coating
- Electrocoat

- Spray
- Dip/spin
- Autophoretic dip
- Convective cure

A copy of the finished survey shall be included in the PPAP package. An updated copy must be submitted each year or as agreed upon at the site level.

# **Section 5.0 Manufacturing/Process Control**

Return to top

Suppliers shall provide appropriate training to ensure that employees are competent and qualified to produce quality deliverables.

Supplier's product or service shall meet all statutory and regulatory requirements for the locations where it is manufactured and used. These requirements shall be properly documented, and records maintained.

Suppliers shall plan and operate a comprehensive maintenance system for the production equipment used to support products.

Suppliers shall monitor the performance of their manufacturing processes to demonstrate compliance with MacLean Power Systems requirements for product quality and efficiency of the process. Adopting Lean Manufacturing Principles is encouraged.

Section 5.1 Control Plan	Return to
	<u>Top</u>

MacLean Power Systems suppliers are required to control all manufacturing processes in accordance with the control plan, which is approved during part qualification. Supplier's control plan shall identify all MacLean Power Systems requirements and the method of inspection and when applicable, functional verification shall be performed. MacLean Power Systems may specify certain criteria for inspection methods and functional verification. The control plan establishes the method and frequency of monitoring and measuring the product

<b>*</b>	MacLean	MacLe Supplier I	an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

and processes to ensure conformity to MacLean Power Systems requirements. Suppliers shall establish procedures to control non-conforming product or service. The non-conforming product shall not be released or delivered unless approved by MacLean Power Systems.

Section 5.2: Statistical Process Control (SPC)	Return to
	<u>Top</u>

Suppliers shall demonstrate process capability through statistical controls for all designated special characteristics and maintain control for all measurement methods used. The target process capability for special characteristics shall be (Cp, Cpk, Pp, Ppk):

- Short-term Cpk greater than or equal to 1.67
- Long-term Ppk greater than or equal to 1.33

Characteristics should be mutually agreed upon by MacLean Power Systems and suppliers and chosen during Advance Product Quality Planning (APQP). Characteristics should be based on product function, design intent, fit, manufacturing process or other factors, which may contribute to an out-of-control condition. When key product/control characteristic designation is identified on drawings, specifications, supply agreements, or purchase orders provided by the customer, suppliers are required to maintain statistical data on that characteristic and be capable of providing it to a requesting site Purchasing and/or Quality as requested. MacLean Power Systems Purchasing and Quality must approve the chosen key product/control characteristics affecting manufacturing processes.

Additional statistical information may be requested for assistance during problem solving or for variation reduction initiatives.

Section 5.3:	Raw Material / Chemical Supplier Statistical Data	Return to
		<u>Top</u>

All Suppliers must maintain (as applicable) SPC data on existing COA data and be prepared to provide it when requested by site Quality or a using plant.

Lab evaluation of the supplied product by a MacLean Power Systems "designated lab" or an agreed upon supplier with a current IATF 16949 registration can conduct the evaluation themselves. Other suppliers must utilize a 3<sup>rd</sup> party lab registered to ISO 17025.

Section 5.4: Gauges	Return to
	<u>Top</u>

Suppliers shall implement a calibration and verification system or procedure to ensure all gauges, jigs, fixtures, poka-yoke devices, measuring, and testing equipment are qualified at

<b>*</b>	MacLean TM POWER SYSTEMS		an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

defined frequencies. Records shall be maintained for all gauges, measuring and testing equipment. An MSA shall be conducted on all new or modified measurement systems. Refer to the AIAG MSA manual for additional information.

If calibration and certification is not within the lab scope of the supplier, this process must be performed by a certified  $3^{rd}$  party.

Section	n 5.5: Control of Nonconforming Product	Return to
		Тор

Suppliers shall properly identify product throughout the realization process. Suppliers shall create a traceability method for unique identification of each part or material lot. Suppliers should utilize an inventory management system to optimize inventory, reduce risk of obsolete product, and ensure first in first out stock rotation.

Suppliers shall identify and control, in a quarantined location, any non-conforming product when product requirements are not met; packaging is incorrect; labeling or marking misidentifies the product and/or when the product status is unknown or suspect.

Suppliers shall implement a procedure to define the controls, related responsibilities, and authority to manage non-conforming product. The non-conforming product must be controlled until suppliers can determine and eliminate root cause of non-conformance through process improvements.

Suppliers shall create process work instructions to define and control rework and repair processes. Any rework or repair process, not identified within the approved PPAP documents, must be approved by MacLean Power Systems prior to beginning. Customer approval does not relieve suppliers of any liability regarding product quality. All corrected non-conforming product must be re-verified to demonstrate conformity to the requirements. Suppliers must properly identify each product or package as repaired or reworked.

If shipment of non-conforming or suspected non-conforming product has been detected by suppliers and is in transit or has been delivered to MacLean Power Systems, suppliers must immediately notify, the site Quality and Purchasing representative at the respective MacLean Power Systems receiving location.

Section 5.6: Containment Policy	Return to
	<u>Top</u>

All suppliers are required to have a containment process to provide additional verification – outside normal processes, prior to shipment. The process must include identifying containment actions, isolating concerns, data collection and implementing corrective actions.

<b>*</b>	MacLean TM POWER SYSTEMS		an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

A "green" dot sticker (or as otherwise specified and agreed to) must be placed near each container label, signed by the Plant Manager or a management designee to indicate the product has been inspected/tested to be 100% defect free.

Exit criteria will be determined on an individual basis by the respective MacLean Power Systems site Purchasing and Quality.

Containment is required (as per the defined and approved Control Plan) for new production start-up and engineering changes to contain any failure modes.

Section 5.7: Controlled Shipping 1	Return to
	<u>Top</u>

Level I containment requires suppliers to implement extraordinary inspection of product to contain a specific failure. Containment actions must verify that requirements are met and be approved by the MacLean Power Systems production facility. This containment must be performed away from the production process in a designated area. Once assigned, suppliers cannot exit this containment without written authorization from MacLean Power Systems.

Section 5.8: Controlled Shipping 2	Return to
	Top

Level II containment requires suppliers to use an independent third party approved by MacLean Power Systems Quality and plant to inspect product prior to release for shipment to the MacLean Power Systems production facility. Controlled Shipping 2 (CS2) containment is initiated once supplier fails to contain non-conforming product within his or her own facility. MacLean Power Systems has the right to require third party inspection to be conducted offsite. Once assigned, suppliers cannot exit this containment without written authorization from Maclean Power Systems.

# Section 6.0: Change Control Return to top

Suppliers are never permitted to knowingly ship product that deviates from the print, specification limits, or design intent without written authorization from MacLean Power Systems. If such a condition exists, the supplier may request MacLean Power Systems to allow shipment of the product. This is accomplished obtaining an approved deviation request.

The supplier must have a documented system for assuring that the latest MacLean Power Systems drawings are available and in use at their facility. The supplier's quality management system must contain a documented procedure that describes the method used for the receipt, review, distribution, and implementation of all changes to drawings

<b>*</b>	MacLean TM S Y S T E M S	MacLe Supplier F	an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

and specifications. In addition, the procedure must address control of obsolete drawings and specifications. A documented procedure should also detail the method used to contain new or modified parts until approved by the customer.

MacLean Power Systems site Quality at the respective receiving facilities must approve all changes to product and/or process in advance. Suppliers who make unapproved changes will be liable for all warranty costs, rejection costs incurred by MacLean Power Systems and/or their customers. All changes must have PPAP approval prior to implementation (unless otherwise agreed to in writing).

Samples may be required for review and to evaluate potential impact on MacLean Power System's manufacturing processes.

Level 3 PPAP Submission approval is required unless specifically waived in writing by MacLean Power Systems Location Purchasing and Quality.

Suppliers requesting the change shall be responsible for all validation costs incurred by MacLean Power Systems, including PPAP costs should MacLean Power Systems have to redo their submissions to their customer.

Section 6.1: Product / Process / Location Changes	Return to
	<u>Top</u>

All production location changes to product and/or process must be requested and approved in writing in advance by MacLean Power Systems site Purchasing and Quality personnel.

The move plan must be submitted to and approved in writing by the respective MacLean Power Systems Quality personnel.

The move plan must include the requirements of a production bank as necessary to ensure MacLean Power Systems' production and service requirements are not affected. Maclean Power Systems Logistics will establish the requirements for this production bank and on-site confirmation of the bank may be required before the move can occur.

Level 3 PPAP submission and approval is required as defined in the latest AIAG PPAP manual prior to the shipment of production material from the new location.

Sec	ion 6.2: Extended Shutdown	Return to
		<u>Top</u>

All MacLean Power Systems receiving locations must be notified in writing a minimum of 30 business days prior to an extended production shutdown (unless stated otherwise in terms and conditions). Examples of extended shutdown/start-up periods include customer

<b>*</b>	MacLean TM S Y S T E M S	MacLe Supplier	an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

changeover, scheduled preventative maintenance for tooling, machinery or processes or the anticipation of a work stoppage due to Union Contract Negotiations.

Section 6.3: Build Out / Obsolescence	Return to
	<u>Top</u>

Suppliers shall have established detailed plans in place with defined responsibilities to manage build outs and engineering changes to minimize obsolescence.

MacLean Power Systems may be responsible to purchase raw material and finished goods that the supplier has been authorized to purchase and produce, according to the agreed upon terms and conditions.

Suppliers shall have fifteen days from the end of production to file an obsolescence claim with MacLean Power Systems. MacLean Power Systems will validate the claim and verify the totals prior to submission of the claim to the end customer. It is the responsibility of suppliers to verify the obsolescence claim terms with the appropriate person at the affected MacLean Power Systems site to ensure that their claim is submitted within the appropriate timeline for payment. The affected MacLean Power Systems site may audit the obsolete material at supplier to validate the claim. This material must be put in an area that allows complete access to all containers, so that it can be readily counted. Failure to make the material available for count may negate suppliers' obsolescence claim.

The supplier may receive payment for the obsolescence claim once the affected MacLean Power Systems site has received payment from the end customer.

# Section 7.0: Rejected Product and Corrective Action Return to top

Suppliers should adopt the "Zero Defects" mindset to reduce and eliminate non-conformances. When a non-conformance occurs, the goal is to identify the problem, minimize its impact, determine the root cause, implement corrective actions, and prevent recurrence quickly and effectively.

A robust problem-solving methodology leads to effective root cause identification and elimination. MacLean Power Systems recommends the 8D Problem Solving method. Verification of root cause identification and elimination requires 21 days of verification.

Error-proofing methods are effective corrective actions to eliminate recurrence of a root cause when properly implemented. Suppliers shall use error-proofing methods to identify potential design and/or process improvements and implement when applicable. Refer to the AIAG CQI-20 document for additional information on problem solving. Refer to the AIAG CQI-18 document for additional information on error-proofing.

<b>*</b>	MacLean	MacLe Supplier I	an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

MacLean Power Systems may issue a S-CAR & Chargeback/Debit in the identification and resolution of non-conformance detected at a MacLean Power Systems facility and/or customer. The S-CAR & Chargeback/Debit may be issued based upon incoming inspections, in-process rejects, customer rejects, field failures, packaging, or labeling issues.

Suppliers are expected to respond to all S-CAR & Chargeback/Debit issued.

For example, when a supplier receives a S-CAR & Chargeback/Debit, MacLean Power System's 24-14-30 policy shall be adhered to. The 24-14-30 Policy is as follows (or as otherwise agreed to).

Section 7.1: Initial Response within 24 hours	Return to
	Top

- 1. Acknowledge receipt of S-CAR upon notification
- 2. Identify all suspect product
- 3. Notification of quantity of suspect material in route to MacLean Power Systems and/or its customers
- 4. Immediate containment action taken (including an objective sort to include S-CAR# on certification documentation)
- 5. Interim plan for supporting MacLean Power Systems production with certified product

Section 7.2 Corrective Action Plan	an within 14 Days (Target)	Return to
		Top

- 1. Use problem solving techniques to determine the root cause of the nonconformance
- 2. Detailed plan for implementing corrective actions to control and prevent recurrence
- 3. Disposition of suspect products

Section 7.3 Final Report within 30 Days (Target	Return to
	Тор

- 1. Implemented corrective actions with supporting data
- 2. Verify effectiveness of corrective actions

If suppliers fail to respond appropriately, suppliers may be placed on New Business Hold.

There will be no time limit for rejection of production materials. Components and/or raw materials shall remain viable for use throughout the life of a program, regardless of when they were purchased, unless a shelf-life period is assigned and agreed to with MacLean

<b>*</b>	MacLean TM		an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

Power Systems, prior to a written purchase order being given for the materials. Any material that is found to be discrepant at time of use, will be returned to suppliers, through the issuance of the S-CAR.

MacLean Power Systems will determine freight method while minimizing cost to suppliers but will ensure that the end customer does not suffer material shortages. Suppliers will get shipping instructions from MacLean Power Systems to replace rejected material. This will be based on customer coverage.

Section 8.0: Packaging, Labeling & Delivery	<u>Return to</u> <u>top</u>
Section 8.1: Packaging	Return to Top

The choice of packaging could have a significant effect on product quality and is to be considered during feasibility evaluation. Shipping trials must be conducted to evaluate the ability of the packaging to preserve product quality. Packaging must be approved, and suppliers shall not make changes without prior approval by the responsible MacLean Power Systems site Logistics and/or Quality contacts.

Containers shall be ergonomically designed to reduce the exposure to injury when handling pallet-sized containers. Containers shall conform to AIAG size standards. For less than pallet-sized containers, total package weight, when full, shall not exceed 30 pounds (13.61 kilograms), unless otherwise approved. Protective wrapping or specified pallets may be required by MacLean Power Systems.

All suppliers shall operate under written packaging and labeling procedures in accordance with AIAG standards as well as the customs laws of the received country.

Section 8.2: Returnable Containers	Return to
	Тор

Expendable packaging will not be accepted unless supplier obtains written authorization from the responsible MacLean Power Systems site Logistics contact prior to initial production shipment.

MacLean Power Systems requires packaging, dunnage, and palletizing product to be returnable, reusable, or recyclable. Reasonable care in use and handling of containers shall be exercised.

Chronic problems with container damage may be escalated for resolution to the responsible MacLean Power Systems site Logistics representative.

MacLean MacLea		MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

If supplier is not in possession of returnable containers or the containers received are in poor condition, supplier is to contact the responsible MacLean Power Systems site Logistics contact for direction and resolution.

Section 8.3: Labeling	Return to
	Top

Each separate unit of packaged product shall have labels on the adjacent sides of as otherwise agreed to. Failure to comply with MacLean Power Systems and/or customer requirements on labeling is cause for REJECTION. Suppliers are responsible for all labelling issues related to packaging. At a minimum, a carton label must be on every carton and a master label of every pallet.

Any materials that are controlled or that have a specified shelf life must be clearly identified on the label and contain a "Do Not Use After This Date" notation.

Sample materials shall be clearly identified. Each container of sample material shall have a "SAMPLE MATERIAL, ATTN CONTACT NAME" label affixed to each side of the shipping container. The label shall be of a different shade than the standard shipping label, so that it stands out as sample material. Should sample material be mixed on a pallet with normal production material, the pallet must be clearly labeled as "Mixed pallet, sample material enclosed". The Bill of Lading for a shipment that contains sample material must have the sample material on the shipment clearly identified, and must contain the phrase "SAMPLE MATERIAL, ATTN CONTACT NAME", clearly identified on the paperwork alongside the part number.

Due to the variety of products purchased and manufactured by MacLean Power Systems, component suppliers shall use barcode shipping labels (reference AIAG Shipping/Parts Identification Label Standard, AIAG-B-3). These labels require all the following information, unless other arrangements have been made with MacLean Power Systems /site Purchasing:

- Unit of measure (as specified by MacLean Power Systems P.O.)
- Supplier name and shipping location
- Quantity (net and allowance where applicable)
- Pack date
- Ship date
- Ship to address
- Shipping terms (FOB, CIF, etc.)

- Customer inventory code number
- Shade code (if applicable)
- Latest engineering level
- Serial number
- Purchase order/shop order
- Weight: net, tare, gross
- Product description
- Country of origin
- Customer part number
- Lot number(s)

MacLean TM POWER SYSTEMS		MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

Section 8.4: Raw Material / Chemical Suppliers	Return to
	<u>Top</u>

Containers smaller than a tanker/bulk shipment are to be labelled with the following information unless other agreed to with the respective MacLean Power Systems receiving site.

- Date of manufacture
- Net weight

- Lot numbers
  - Product identification

Compliance to all legislative and regulatory labeling requirements, including proper identification of all hazards materials and subsequent handling requirements is mandatory.

To prevent mislabeling concerns on returnable containers, it is supplier's responsibility to remove all old labels, or to place new labels over the old labels in such a manner as to completely cover all the information from the old label. Returnable totes must have the control label applied on the release placard between the identification labels.

When multiple lot numbers are being shipped, suppliers shall list the lot numbers on the bill of lading.

Section 8.5: Inventory Contro	ol Labels	Return to
		<u>Top</u>

All materials suppliers must be shipped in date-produced order using a first in, first out (FIFO) inventory management system.

All chemical suppliers must provide a "Use By, date" on each label.

Chemical suppliers must ensure that a minimum of six months shelf life be available for all products shipped into MacLean Power Systems sites unless specific written authorization is received from the respective MacLean Power Systems using site prior to shipment.

Shelf-life requirements shall be from date of manufacture, not date of shipment.

Suppliers shall be responsible for all costs incurred due to shipment of material outside of the usage window.

Section 8.6: Releases	Return to
	<u>Top</u>

Failure to receive a release does not constitute reason for short shipment. When a supplier does not receive a release on time, suppliers shall notify Maclean Power Systems

MacLean TM POWER SYSTEMS		MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

Purchasing, while using the previous week's release and adhering to the same dates required. Suppliers shall review the new release when received and notify Maclean Power Systems if there is any chance that the release cannot be met.

Suppliers are expected to meet the lead-time CUM (cumulative demand) required. Reduction in CUM, required within the lead time will not be accepted by the customer as a valid reason to short ship.

MacLean Power Systems will not be responsible for any storage charges due to decreased releases from our customer and may not accept any over-shipments (unless otherwise agreed to, plus or minus ten percent for actual shipping quantity versus P.O. may be acceptable). MacLean Power Systems will continue to work with the customer and supplier to resolve release volatility issues.

If non-delivery, delayed deliveries, or short shipments are anticipated, ALL suppliers must immediately notify the respective MacLean Power Systems site Logistics contact. Supplier concerns regarding meeting volume increases must be communicated to the responsible receiving MacLean Power Systems site **within 24 hours** (or sooner) of receipt of the release.

Suppliers must be able to handle release accounting. Releases will be sent weekly, unless otherwise agreed to, and will go out as far as our customer releases. Releases will show cumulative requirements and must be reconciled jointly between the supplier and customer releases. Suppliers will provide proof of delivery (i.e. shipping documents) to reconcile CUM's. Suppliers are responsible to inform MacLean Power Systems of any known discrepancies.

Section 8.7: Customs	Return to
	<u>Top</u>

All shipments shall be accompanied by the proper customs documentation to ensure border crossing. Shipping documents (packing slip, bill of lading, commercial invoice) will reference MacLean Power Systems part number and product description. If documentation is missing or incomplete, suppliers shall assume all subsequent costs.

All customs documentation, including commercial invoice, must be emailed to MacLean Power Systems Customs Broker when load leaves supplier's dock.

If further information is required, suppliers shall contact the respective MacLean Power Systems site Logistics contact at the receiving location.

Every January the supplier shall supply USMCA Certificate of Origin to the MacLean Power Systems Customs Broker for all materials supplied.

MacLean TM POWER SYSTEMS		MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	H
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

It is a MacLean Power Systems requirement that all suppliers provide accurate documentation with their shipments to any MacLean Power Systems site or subsidiary location.

A consistent paper trail consisting of the invoice, commercial invoice, packing slip and/or bill of lading, and purchase order, shall be maintained in order to avoid penalties.

Any discrepancies in quantity, pricing, or other pertinent information, shall be reported to MacLean-Power Systems Customers Broker within three days of the shipment. Failure to properly report discrepancies shall result in suppliers being charged any and all penalties.

This charge shall be issued to suppliers via S-CAR & Chargeback/Debit and will be added to Suppliers Rating system. The charge will be deducted from the next payment to the supplier.

MacLean Power Systems receiving sites shall audit all inbound shipments for compliance and will report any discrepancies directly for resolution. Any related charges shall be charged to suppliers via S-CAR & Chargeback/Debit.

Suppliers must cooperate promptly and fully with MacLean Power Systems in providing any back-up information that may be needed to respond to inquiries from U.S. Customs and Border Protection or other U.S. federal agencies about such issues as country of origin, tariff classification, manufacturer's identification, or eligibility for preferential tariff programs. Back-up information that may be needed can include materials costing and sourcing, production records, and accounting information.

Section 8.8: In-Bound Freight	Return to
	<u>Top</u>

Suppliers shall have a program in place with their suppliers, which allows, at any time, for carrier assignment and tracking of in-bound products. Suppliers' material control activity shall assure raw material and component availability through documented communication between production, manufacturing, and purchasing activities related to the shipment at all MacLean Power Systems sites.

Section 8.9: Out-Bound Freight	Return to
	Top

Unless otherwise specified, the customer shall be responsible to coordinate freight carrier and schedule. Suppliers are required to use customer-designated carriers; however, suggestions for improvement may be forwarded to the respective MacLean Power Systems site Logistics representative.

MacLean TM POWER SYSTEMS		MacLean Power Systems Supplier Requirements Manual	
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

When utilizing the customer freight lines, supplier shall assume all charges associated with truck "wait time" in excess of  $\frac{1}{2}$  hour of the appointed arrival time at supplier's facility.

Suppliers receiving load sheets must contact the respective MacLean Power Systems site logistics person if all the requirements on the load sheet cannot be shipped before the truck is released.

Any charges generated using an unauthorized/unapproved carrier shall be at supplier's expense.

All charges that appear on freight bills that are paid by the supplier must be the actual charges incurred and proof of actual payment of such charges must be made available to any Maclean Power Systems facility upon request for a period of up to five (5) years after payment.

Section 8.10: Physical Condition	Return to
	<u>Top</u>

All trailers are expected to be clean and in good useable condition. Any trailer damage shall be reported to the carrier prior to loading of product.

Damage to the load due to faulty carrier equipment or damage while in transit shall be reported to suppliers by the receiver and addressed through an insurance/damage claim filed by suppliers against the carrier.

Section 8.11: Unloading and Transfer of Transfer Materials	Return to
	Top

All suppliers shall comply with unloading procedures established at each MacLean Power Systems facility. Suppliers shall have appropriate training in the use of the transfer equipment, personal protective equipment (PPE) and chemical hazards.

Supplier is to provide his or her own PPE in accordance with the facility procedure and hazards of the material being transferred.

In the event of an emergency, all suppliers shall follow plant emergency procedures. It is the responsibility of Supplier to become familiar with the procedures at each MacLean Power Systems location they supply.

<b>*</b>	MacLean	MacLe Supplier I	an Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

Section 8.12: C-TPAT (Customs-Trade Partnership Against Terrorism)	Return to
	<u>Top</u>

All suppliers shall complete the C-TPAT questionnaire when requested by MacLean Power Systems (as applicable or as otherwise agreed to). This questionnaire must be returned within thirty days of the request.

Suppliers may receive an on-site visit to verify C-TPAT compliance.

# **Section 9.0 Cost of Poor-Quality Recovery Policy**

Return to top

Suppliers are liable for all costs incurred by MacLean Power Systems and end use customers when the cause is deemed to be the supplier's responsibility.

Upon the receipt of a S-CAR Request & Chargeback/Debit, suppliers will provide authorization for disposition within 1 week. Failure to make disposition within 1 week, will empower the using plant to make disposition at supplier's cost. All materials returned, reworked and/or scrapped may be counted against supplier's quality performance on the supplier scorecard.

If a supplier does not agree with the S-CAR Request & Chargeback/Debit, an appeal can be made to the respective MacLean Power Systems site Quality contact.

Suppliers shall be debited for any/all product failure costs determined to be the responsibility of suppliers, regardless if failure occurred prior to or after shipment to the end/final customer. Product, logistical and service non-conformances/complaints will be reported using a S-CAR. This form will also be used to inform suppliers of the request for written corrective and preventive action using a S-CAR Request & Chargeback/Debit.

Charges to suppliers will be based on local rates at the affected MacLean Power Systems site(s).

Section 9.1 Other Charges	Return to
	<u>Top</u>

The following types of charges shall be calculated on the actual time and costs incurred for the associated action:

- Rework, repair, scrap supplier fault
- Dispositioning of supplier fault scrap
- Premium freight costs including air charter if required
- Overtime to avoid production interruption

<b>1</b>	MacLean TM POWER SYSTEMS		ean Power Systems Requirements Manual
Document #:	COR-PLCY-00002	Revision:	Н
Owners:	Corporate Director of MFI	Effective Date:	Aug 17, 2023

- Production down time for Maclean Power Systems and its end customer
- Sorting of suspect material in-house, at customer location or third party and contractor costs
- On-line containment
- Tear-down (Minor, Major, and Complete) and outside lab testing
- Customer returns including hourly charges, transportation and on-site inspection services
- Meeting customer environmental reporting and documentation requirements
- Receiving inspection, material handling and freight associated with scrap and replacement material
- Transportation waiting charges, trailer storage charges



# Appendix A: MPS Supplier Requirement Manual Sign Off Return to top By signing this form, we as a supplier acknowledge and accept the requirements outlined in the MacLean Power Systems Supplier Requirement Manual. Supplier Name

Supplier Name	
Supplier Address	
_	
Name (print)	
•	
Name Signature _	
Date	